

iPP 200 series

The intuitive desktop PIN Pad for PIN entry and contactless payment

- Accelerate secured payment at the counter with consumer facing contactless and PIN entry solutions.
- Integrate the very compact iPP 200 series into any counter-space.
- Connect the iPP 200 series to any countertop in a few seconds thanks to plug & play installation.



security



contactless



color backlit

Easy to integrate into any counter-space, the iPP200 is an intuitive PIN Pad with consumer-facing contactless & PIN entry solutions.

Highest Security

The iPP200 series meets the latest hardware and software security requirements including: PCI-PTS 2.x and 3.x. Also complies with SRED and open protocol modules. The optional PIN privacy shield guarantees confidentiality of PIN entry.

PIN Entry and Contactless

Offering secured PIN entry and Contactless payment, the iPP200 series also allows NFC new payment add-ons such as loyalty programs, couponing and wallets use cases.

Designed for Merchants

Slim and lightweight, optimized for fast check-out, the iPP200 series is designed to meet merchant environment needs. Very compact, the iPP200 series takes up minimum counter space. Color backlit display, 15-key keypad, and 4 function keys provide day-to-day convenience and comfort.

Enhanced Readability

iPP280 integrates a 4-line-display with adjustable color backlight to enhance readability for consumers.

Easy Connectivity

Integration with Ingenico ICT series has never been easier thanks to the iPP200 series' powered USB connection.

Telium 2

Powered by Ingenico, Telium 2 technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium 2 is the world's best platform to provide payment services. It provides a fully scalable, reliable operating system embedded into the 22 million terminals deployed worldwide.



NAME		iPP220	iPP280
Processor	ARM 7	●	●
Memory	512 K Flash/96 K SDRAM	●	●
Display		Monochrome	Color backlit display
		2 lines of 16 characters	4 lines of 16 characters
Terminal connectivity		USB 2.0 - Device	USB 2.0 - Device
Keyboard	Operational keys	15	15
	Navigation keys	4	4
Audio	Buzzer	Option if contactless	●
Contactless reader		Option	●
Power supply	Powered USB	5V 500 mA	5V 500 mA
Terminal size	L x W x H	132 mm x 74 mm x 37 mm	132 mm x 74 mm x 37 mm
Weight		145 g	145 g
Environment	Operating temperature	+5°C to +40°C	+5°C to +40°C
	Storage temperature	-20°C to +55°C	-20°C to +55°C
	Relative humidity, non condensing	85% RH at +40°C	85% RH at +40°C
Optional privacy shield	PCI compliant	Additional privacy shield	Additional privacy shield
	ZKA, PCI+ compliant	Factory option	Factory option
Security	Online & Offline	PCI-PTS 3.x	PCI PTS 2.x & 3.x



www.ingenico.com

ingenico
Smart terminals